



Ecovent® 140 is a vapour-permeable roofing underlay suitable for unboarded warm and cold pitched roofs.

Product features & benefits

- Vapour permeable
- Three-layer material
- CE certified for non-ventilated cold and warm roofs
- No additional ventilation required
- Allows roof structure to breathe yet fully waterproof
- Limits air leakage in a sealed roof application

Area of application

Suitable for unboarded cold and warm roofs.

Material

Laminated sheet material, with outer layers of polypropylene, and an inner layer of polyethylene.

Roll sizes

50 x 1.5m (75m²)

Packaging

20 rolls/pallet

Product code

KU 1080

Certification

- CE certified



TECHNICAL DATA



Weight	140g/m ²	
Water vapour transmission EN 12572 (s _d value)	0.03m	
Reaction to fire EN 13501-1, EN 11925-2	E	
Water column, EN 20811	> 2500mm	
Resistance to water penetration EN 1928	W1	
Tensile strength longitudinal / transverse EN 12311-1	250N/50mm	230N/50mm
Elongation longitudinal / transverse EN 12311-1	60%	75%
Resistance to tearing (nail shank) longitudinal / transverse EN 12310-1	180N	180N
Resistance to temperature	-40°C to + 80°C	

TS-09#52-EN-1012. Für Druckfehler wird keine Haftung übernommen. ®Eingetragenes Warenzeichen der Klöber GmbH.