



Permo[®] TR plus is an essential product for reducing energy loss through the roof. It is a multifunctional adhesive tape, ideal for creating airtight seals between laps in underlays or vapour control layers/air barriers, repairing holes in underlays/vcls and sealing around pipe sealing collars.

Product features & benefits

- Single-sided transparent tape
- Includes a reinforcement mesh for strength
- Multi-functional tape, used for joining, repairing and creating airtight seals
- Ideal for use with Wallint[®] solar since it maintains its low emissivity properties
- Extremely durable

Area of application

Suitable for:

- Repairing holes/tears in underlays or vapour control layers/air barriers
- Sealing laps between underlays or vapour control layers/air barriers
- Creating a seal around sealing collars
- Around roof penetrations
- Butt joints
- Timber frame: planed/finished or stained
- Synthetic materials: paper, fleece or similar, PE, PP or hard PVC
- Other surfaces: metal, glass, PUR-foam/styrofoam
- Use both internally & externally
- All pitches of roof

Material

Acrylic adhesive with PE release paper

Product codes

KU 0121-1 (25m x 60mm wide)

Packaging/Weight

10 rolls per carton/3.8kg

Related products

- Any Klober underlay
- Wallint[®] or Wallint[®] solar vapour control layers/air barriers
- Permo[®] extreme RS SK²
- Pipe sealing collar

TECHNICAL DATA

Adhesive	Acrylic
Solvent	None
Installation temperature	> +5°C
Temperature stability	-40 to +100°C
UV resistance	3 months
Resistance to ageing	Acrylic adhesive does not dry out or become brittle. It remains permanently elastic & adhesive.
Shelf life	12 months at ≤30°C
Thickness	0.3mm

TS-09#61-UK-0415. We assume no liability for typing errors.